

ASME/CSA Standard

*ASME A112.18.1-2005
CSA B125.1-05
Plumbing supply fittings*



The American Society of
Mechanical Engineers[®]



[®]
**CANADIAN STANDARDS
ASSOCIATION**

[®]Registered trade-mark of Canadian Standards Association

Contents

ASME Standards Committee A112 on Plumbing Materials and Equipment *vi*

ASME Project Team 18.1 — Plumbing Fixture Fittings *viii*

CSA Technical Committee on Plumbing Fittings *x*

ASME/CSA Joint Harmonization Task Group on Plumbing Fittings *xii*

Preface *xiii*

CSA Foreword *xv*

1 Scope 1

2 Reference publications 2

2.1 ASME and CSA publications 2

2.2 Other publications 2

3 Definitions and abbreviations 4

3.1 Definitions 4

3.2 Abbreviations 7

4 Design requirements 8

4.1 Supply fittings 8

4.1.1 Rated pressure 8

4.1.2 Rated temperatures 8

4.1.3 Seating members 8

4.2 Servicing 8

4.3 Installation 8

4.4 Threaded connections 9

4.5 Connections other than threaded connections 9

4.6 Accessible design 9

4.7 Backflow prevention 9

4.8 Cover plates and escutcheons 10

4.9 Toxicity 10

4.10 Frost-proof faucets and hydrants 10

4.11 Shower heads, body sprays, and hand-held showers 10

4.12 Cross-flow 10

4.13 Fittings incorporating electrical features 10

4.13.1 General 10

4.13.2 Testing 11

4.14 Materials 11

4.15 Automatic compensating valve temperature control 11

4.16 Lawn and sediment faucets 11

5 Performance requirements and test methods 11

5.1 General 11

5.1.1 Preconditioning 11

5.1.2 Installation for testing 11

5.1.3 Applicable tests 11

5.2 Coatings 11

5.2.1 General 11

5.2.2	Corrosion (all substrates and coatings)	12
5.2.3	Adhesion	12
5.2.4	Decorative organic coatings	13
5.3	Pressure and temperature	14
5.3.1	Static and dynamic seals	14
5.3.2	Burst pressure	14
5.3.3	Cross-flow check valves	15
5.3.4	Hose assemblies	15
5.3.5	Ball joints	15
5.3.6	Diverter	15
5.4	Flow rate	16
5.4.1	Supply fittings	16
5.4.2	Test procedure	16
5.5	Operating requirements	16
5.6	Life cycle	17
5.6.1	Requirements	17
5.6.2	Test method	18
5.6.3	Fittings and other control devices	19
5.6.4	Swing spouts	20
5.6.5	Shower hoses, pullout spout hoses, and side spray hoses	20
5.7	Resistance to installation loading	21
5.7.1	Bending strength	21
5.7.2	Thread torque strength	21
5.8	Resistance to use loading	21
5.8.1	Operating controls	21
5.8.2	Maintenance of installed position	21
5.8.3	Swing spout strength	22
5.9	Backflow prevention	22
5.9.1	General	22
5.9.2	Fittings with plain outlets	22
5.9.3	Fittings with a submersible outlet(s)	23
5.9.4	Backflow prevention devices used in single-outlet fittings with a submersible outlet	23
5.9.5	Back siphonage prevention in side spray diverters	25
5.10	Automatic compensating valves	26
5.10.1	General	26
5.10.2	High-temperature conditioning test	26
5.10.3	Pressure and burst pressure test	26
5.10.4	Maximum torque and/or force adjustment	27
5.10.5	Life cycle test	27
5.10.6	Temperature control	28
5.10.7	Supply line pressure loss	30
5.10.8	Temperature and high limit control	30

6 Markings 31

6.1	General	31
6.2	Temperature identification	31
6.3	Packaging	31
6.4	Instructions for automatic compensating valves	31

Annexes

A (informative)	— Unit conversion criteria	42
B (normative)	— Tests by fitting type	43
C (informative)	— Verifying the time constant of the temperature-measuring equipment	45
D (informative)	— Temperature variation for pressure- and thermostatic-compensating valves	47

Tables

- 1** — Minimum and maximum flow rates 32
 - 2** — Operating requirements 33
 - 3** — Life cycle test 33
 - 4** — Thread torque strength 34
-

Figures

- 1** — Deck-mounted lavatory and sink supply fittings 34
- 2** — Dimensions for 1/2-14 NPSM shanks 35
- 3** — Bending loads on supply fittings 36
- 4** — Discharge capacity test schematics 37
- 5** — Set-up for check valve leakage test 38
- 6** — Set-up for back siphonage and hidden check valve test 39
- 7** — Set-up for high-temperature conditioning, regulation and temperature variation, and cold water supply pressure loss tests 40
- 8** — Set-up for life cycle test for automatic compensating valves 41